



### Product Specification Sheet - IC 330 G

	<b>Product</b>		<b>Inner Container 330 G with QD Ball Valve &amp; Non Vented Lid (Solid)</b>	
	<b>Material</b>		High Density Polyethylene	
	<b>Dimensions</b>		Length: 1155 MM (+/- 5 MM) Width: 970 MM (+/- 5 MM) Height: 1190 MM (+/- 5 MM)	Length: 45.5" (+/- 0.19") Width: 38.12" (+/- 0.19") Height: 47" (+/- 0.19")
	<b>Tare Weight</b>		18.0 KG +/- 3 KG	36.5 lbs
	<b>Capacity</b>		Nominal: 1250 Liters Brimful: 1265 Liters	Nominal: 330 Gallon Brimful: 334 Gallon
		<b>Filling Opening</b>	<b>Material</b>	Filling Opening DN 150 with NPS/ buttress type threading. Provision of 50/70 mm bung with/ without venting device covered with seal cap.
Screw-cap DN 150:				PE- HD, Black
Gasket in 150 mm				EPDM
Plug				PE-HD
Gasket in 50 mm NPS plug				EPDM
Vent:				No
	<b>Discharge Opening</b>	<b>Material</b>	High quality 2" Ball Valve with Viton Gasket, discharge end sealed with PE/AL foil closed with end cap.	
			Body	PE, Black
			Screw-cap:	PE, Yellow
			Neck Gasket	EPDM/ Viton/ PE (Options)
			Body Gasket	PE
			Screw for Earthing	NA
<b>Printing / UN- Marking</b>		31 HA1/Y/... UN approved		

Note- The information provided in this paper is believed to be true and accurate at the time of publication, based on our current knowledge. While we may not make any changes to this specification, we reserve the right to do so in order to improve the product's performance.