



Product Specification Sheet - IC 275 G

DESCRIPTION: 275 GALLON / 1000 LITER, UN, UV STABILIZED, WITH HDPE INNER CONTAINER, DN 150 CAP 2" PLUG, DN 50 BALL VALVE, INNER CONTAINER

	Product		Inner Container 275 G with QDV - G2V	
	Dimensions		Length: 1155 MM (+/- 5 MM) Width: 970 MM (+/- 5 MM) Height: 1000 MM (+/- 5 MM)	Length: 45.5" (+/- 0.19") Width: 38.12" (+/- 0.19") Height: 39.37" (+/- 0.19")
	Tare Weight		15.0 KG +/- 3 KG	33.06 lbs
	Material		High Density Polyethylene	
	Filling Opening	Material	Filling Opening DN 150 with NPS/ buttress type threading. Provision of 50 mm bung with venting device covered with seal cap in Yellow color.	
			Screw-cap DN 150:	PE- HD, Black
			Gasket in 150 mm	EPDM
			Plug	PE-HD
			Gasket in 50 mm plug	EPDM
			Vent:	Yes (D15 Membrane)
	Discharge Opening	Material	High quality 2" Ball Valve with Viton Gasket, discharge end sealed with PE/AL foil closed with end cap.	
			Body	PE, Black
			Screw-cap DN 50:	PE, Yellow
			Neck Gasket	EPDM/ Viton/ PE (Options)
			Body Gasket	PE
			Screw for Earthing	NA
Printing / UN- Marking		31 HA1/Y/... UN approved		

Note- The information provided in this paper is believed to be true and accurate at the time of publication, based on our current knowledge. While we may not make any changes to this specification, we reserve the right to do so in order to improve the product's performance.