

SENSOR FLOAT® MINI Control Switch

Mercury activated, narrow-angle float switch designed to activate pump control panels and alarms.

This narrow-angle sensing device is used to accurately monitor liquid levels in confined sewage and non-potable water applications. The **Sensor Float® Mini** control switch is not sensitive to rotation.

Normally Open Model (high level)

The control switch turns on (closes) when the switch tips slightly **above** horizontal signaling a high level, and turns off (opens) when the switch drops slightly below horizontal.

Normally Closed Model (low level)

The control switch turns on (closes) when the switch drops slightly **below** horizontal signaling a low level, and turns off (opens) when the switch tips slightly above horizontal.

Contact SJE Rhombus regarding intrinsically safe applications.



FEATURES

- Designed for use in confined spaces.
- Not sensitive to rotation.
- Control differential of .5 inches (1 cm) above or below horizontal.
- UL Listed for use in non-potable water and sewage.
- CSA Certified.
- Five-year limited warranty.



OPTIONS

This switch is available:

- for normally open (high level) applications or normally closed (low level) applications.
- in standard cable lengths of 10, 15, 20, or 30 feet and 3, 5, 6, or 10 meters (longer lengths available).
- with two mounting options that allow for flexibility in installation:

Mounting Clamp: for applications where the switch can be attached to a discharge pipe or similar mounting device.

Externally Weighted: for applications where the switch can be suspended from above.

SPECIFICATIONS

CABLE: flexible 18 gauge, 2 conductor (UL, CSA) SJOW, water-resistant (CPE)

FLOAT: 2.81 inch diameter x 3.42 inch long (7.14 cm x 8.68 cm), high impact, corrosion resistant PVC housing for use in sewage and non-potable water up to 140°F (60°C)

MAXIMUM WATER DEPTH: 30 feet (9 meters), 13 PSI (90 kPa)

MERCURY TILT SWITCH: single pole, single throw, mercury-to-metal contacts, hermetically sealed in a steel capsule and epoxy sealed in the float housing

ELECTRICAL: 5 amp, 120/230 VAC, 50/60 Hz

This switch is not recommended for controlling:

- electric loads less than 30 milliamps, 12 VAC
- non-arcing electric loads (intrinsically safe applications)

California Prop 65 requires the following:  WARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov

**SEE REVERSE SIDE FOR ORDERING INFORMATION.
SEE PRICE BOOK FOR LIST PRICE.**



SJE RHOMBUS®

1-888-DIAL-SJE • 1-218-847-1317
1-218-847-4617 Fax
email: customer.service@sjeinc.com

www.sjerrhombus.com

G.17

SENSOR FLOAT® Mini Control Switch

Mercury activated, narrow-angle float switch designed to activate pump control panels and alarms.

ORDERING INFORMATION

| Normally Open | | Normally Closed | | Shipping Weight |
|---------------|-------------|-----------------|-------------|-----------------|
| Part # | Description | Part # | Description | |
| 1002181 | 10MPCNO | 1002184 | 10MPCNC | 1.20 lbs. |
| 1002206 | 10MWENO | 1002209 | 10MWENC | 2.58 lbs. |

| | | | | |
|---------|---------|---------|---------|-----------|
| 1002187 | 15MPCNO | 1002190 | 15MPCNC | 1.57 lbs. |
| 1002212 | 15MWENO | 1002215 | 15MWENC | 2.81 lbs. |

| | | | | |
|---------|---------|---------|---------|-----------|
| 1002193 | 20MPCNO | 1002196 | 20MPCNC | 1.90 lbs. |
| 1002218 | 20MWENO | 1002221 | 20MWENC | 3.14 lbs. |

| | | | | |
|---------|---------|---------|---------|-----------|
| 1002199 | 30MPCNO | 1002202 | 30MPCNC | 2.68 lbs. |
| 1002224 | 30MWENO | 1002227 | 30MWENC | 3.96 lbs. |

PC = Pipe Clamp WE = Weighted Externally NO = Normally Open NC = Normally Closed

NOTE: Descriptions are grouped by cable length measured in feet (10, 15, 20, 30).

SEE PRICE BOOK FOR LIST PRICE.

SPECIFICATIONS

CABLE: flexible 18 gauge, 2 conductor (UL, CSA) SJOW, water-resistant (CPE) jacket

FLOAT: 2.81 inch diameter x 3.42 inch long (7.14 cm x 8.68 cm), high impact, corrosion resistant PVC housing for use in sewage and non-potable water up to 140°F (60°C)

MAXIMUM WATER DEPTH: 30 feet (9 meters), 13 psi

MERCURY TILT SWITCH: single pole, single throw, mercury-to-metal contacts, hermetically sealed in a steel capsule and epoxy sealed in the float housing

ELECTRICAL: 5 amp 120/230 VAC, 50/60 Hz

This switch is not recommended for controlling:

- electric loads less than 30 milliamps, 12 VAC
- non-arcing electric loads

NOTE: Contact SJE Rhombus regarding intrinsically safe applications.

OPTIONS

PACKAGING

Bagged - standard
Boxed - optional
Bulk - optional

ADDITIONAL CABLE

Longer cable lengths available. Please call for details.



OTHER INFORMATION

NORMALLY OPEN (HIGH LEVEL) OPERATION

The control switch closes (turns on) when the float tips slightly **above** horizontal signaling a high level, and opens (turns off) when the float drops slightly **below** horizontal.

NORMALLY CLOSED (LOW LEVEL) OPERATION

The control switch closes (turns on) when the float drops slightly **below** horizontal signaling a low level, and opens (turns off) when the float tips slightly **above** horizontal.



SJE RHOMBUS.

www.sjerrhombus.com
customer.service@sjeinc.com

Call or fax your order!

1-888-DIAL-SJE (1-888-342-5753) • Fax 218-847-4617

*Product offering and pricing are subject to change without notice.
Please visit www.sjerrhombus.com for the most current information.*