

*ALL EXTERNAL PIPING MUST BE INDEPENDENTLY SUPPORTED.
*ONLY BASE FITTINGS TO BE LEFT INSTALLED AT TIME OF SHIPMENT PER SII PROCEDURE.
*Consult Snyder's Guidelines for Use and Installation prior to delivery.
Available on-line at www.snyderindustriestanks.com/Technical

ALL DIMENSIONS ARE IN INCHES, NOMINAL, & SUBJECT TO CHANGE WITHOUT NOTICE. ALL DIMENSIONS ON ROTATIONAL MOLDED PARTS ARE SUBJECT TO A \pm 3% TOLERANCE.

DO NOT SCALE	DRAWN BY	CHI CHVDER	TITLE:		REVISION
Released	ВН	INDUSTRIES, INC.	ASM TK 1000VDT X 64		Α
© SNYDER INDUSTRIES, INC., 2018		(402) 467-5221 www.snydernet.com			SHEET 1 OF 1
ALL DIMENSIONS, DESIGNS, AND INFORMATION ON THIS PRINT MUST BE CONSIDERED PROPRIETARY TO SNYDER INDUSTRIES, INC., AND MAY NOT BE USED, COPIED, OR DISTRIBUTED WITHOUT WRITTEN PERMISSION OF AN OFFICER (OR HIS AGENT) OF THE FIRM.		IOLERANCES LINLESS OTHERWISE SPECIFIED ANGULAR = ±1/2° FRACTIONAL = ±1/16" .X = ±0.1", .XX = ±.03", .XXX = ±.010"	PART NO. 1830600N01	D009170	