

TANK SHOULD BE PLACED IN THE CENTER OF THE STAND WITH BLOCKS LOCATED BETWEEN THE TANK AND STAND COLUMNS FOR SUPPORT.

- *ALL EXTERNAL PIPING MUST BE INDEPENDENTLY SUPPORTED.
- *ONLY BASE FITTINGS TO BE LEFT INSTALLED AT TIME OF SHIPMENT PER SII PROCEDURE.
 *TANKS ORDERED WITH FOAM INSULATION WILL HAVE AN INCREASED DIAMETER OF 4-6 INCHES.
- *Consult Snyder's Guidelines for Use and Installation prior to delivery. Available on-line at http://www.snyderindustriestanks.com/Technical

ALL DIMENSIONS ARE IN INCHES, NOMINAL, & SUBJECT TO CHANGE WITHOUT NOTICE. ALL DIMENSIONS ON ROTATIONAL MOLDED PARTS ARE SUBJECT TO A ± 3% TOLERANCE.

000001711 PROTECTIVE PLASTIC PACKAGING 0-200 4 3 1370000N ASM STAND FLAT/CONE 22X12 2 1007700N97802 ASM CNT 90 HD/BLK W/SHELF 1 1000120N___01 ASM TK 35VFT X 18 PUMP ITEM NO. QTY. **PART NUMBER** DESCRIPTION

DO NOT SCALE DRAWN BY STATUS: Released © SNYDER INDUSTRIES, LLC, 2020

SHRINK WRAP NOT SHOWN

ALL DIMENSIONS, DESIGNS, AND INFORMATION ON THIS PRINT MUST BE CONSIDERED PROPRIETARY TO SNYDER INDUSTRIES, LLC, AND MAY NOT BE USED, COPIELO, OR DISTRIBUTED WITHOUT WRITTEN PERMISSION OF AN OFFICER (OR HIS AGENT) OF THE FIRM. (402) 467-5221 www.snydernet.com **ASM TK 35VFT CHEMFEED** W/STAND

REVISION В

SHEET

1 OF 1

1000124N 01 D002933